



Main

Range	Linerigy
Range of product	Linerigy
Product or component type	One-piece connection
Product name	Linerigy BW
Product name	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure Linerigy Linerigy BW busbar
Provided equipment	With connection
Standards	IEC 61439-1, inside enclosure IEC 61439-2, inside enclosure
Product certifications	ASTA

Complementary

Cubicle-device connection	Linerigy BW busbar
Poles description	4P
Installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Pack enclosure - width 550 mm
Installed device	Multi9: NG125 ComPact: NG160 ComPact: INS160 Multi9: C120 Acti 9: iC120
[I _e] rated operational current	160 A
Material	Copper Plastic
Colour	Copper Black (RAL 9005)
Length	165 mm
Net weight	0.48 kg
Quantity per set	Set of 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.4 cm
Package 1 Width	7.8 cm
Package 1 Length	17 cm
Package 1 Weight	472 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.913 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes