LVS04171

Busbar, Linergy BS, 4 threaded bars, 160A, vertical, flat bar, 15x 5mm, L1400mm





Main Range Linergy Range of product Linergy Product or component type Product name Linergy BS Range compatibility PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure Busbar description Flat bar

Set of 4

Complementary

Installation direction	Vertical, operating position: rear	
Installation direction		
Installation description	Cubicle - width 650 mm	
	Floor-standing enclosure - width 600 mm	
	Wall-mounted enclosure - width 600 mm	
	Floor-standing duct - width 300 mm	
	Wall-mounted duct - width 300 mm	
[le] rated operational current	160 A at 35 °C	
[lcw] rated short-time withstand current	10 kA (1 s) for 3 supports	
[lpk] rated peak withstand current	30 kA	
Busbar cross section	15 x 5 mm	
Length	1400 mm	
Width	15 mm	
Depth	5 mm	
Net weight	3.74 kg	
Colour	Natural	
Type of busbar connection	M6 threaded hole	
Connection pitch	Connection each 25 mm	

Quantity per set

Environment

Standards	IEC 61439-2 IEC 61439-1	
Product certifications	ASTA	

Packing Units

1 doking Onits		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.000 cm	
Package 1 Width	17.000 cm	
Package 1 Length	154.000 cm	
Package 1 Weight	3.662 kg	
Unit Type of Package 2	P2M	
Number of Units in Package 2	56	
Package 2 Height	29.000 cm	
Package 2 Width	120.000 cm	

Package 2 Length	200.000 cm	
Package 2 Weight	226.000 kg	
Offer Sustainability		
Sustainable offer status	Green Premium product	

Offer Sustamability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product