



### Main

Range	Linergy
Range of product	Linergy
Product or component type	Busbar
Product name	Linergy BS
Range compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure
Busbar description	Flat bar
Quantity per set	Set of 4

### Complementary

Installation direction	Vertical, operating position: rear
Installation description	Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
[Ie] rated operational current	400 A at 35 °C
[Icw] rated short-time withstand current	20 kA (1 s) for 4 supports
[Ipk] rated peak withstand current	55 kA
Busbar cross section	32 x 5 mm
Length	1400 mm
Width	32 mm
Depth	5 mm
Net weight	8 kg
Colour	Natural
Type of busbar connection	M6 threaded hole
Connection pitch	Connection each 25 mm

### Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.600 cm
Package 1 Width	17.000 cm
Package 1 Length	154.000 cm
Package 1 Weight	8.000 kg
Unit Type of Package 2	P2M
Number of Units in Package 2	56
Package 2 Height	29.000 cm
Package 2 Width	120.000 cm

Package 2 Length	200.000 cm
Package 2 Weight	461.500 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product