



Main

Range	Linergy
Range of product	Linergy
Product or component type	Busbar support
Product name	Linergy BS
Range compatibility	Linergy Linergy BS busbar PrismaSeT PrismaSeT P enclosure PrismaSeT PrismaSeT G enclosure

Complementary

Cubicle-device connection	Linergy BS rear busbar
Installation description	Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing enclosure - width 850 mm Extension enclosure - width 600 mm
Permissible current	160 A - busbar cross section: 15 x 5 mm 250 A - busbar cross section: 20 x 5 mm 400 A - busbar cross section: 32 x 5 mm
[I _{cw}] rated short-time withstand current	10 KA (1 s) at 160 A for 450 mm between support centres 15 KA (1 s) at 250 A for 450 mm between support centres 20 KA (1 s) at 400 A for 300 mm between support centres 25 kA (1 s) at 400 A for 225 mm between support centres
Quantity per set	Set of 1
Net weight	0.24 kg

Environment

Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASTA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	5.300 cm
Package 1 Length	46.300 cm
Package 1 Weight	251.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	6.000 cm
Package 2 Width	51.200 cm
Package 2 Length	52.000 cm
Package 2 Weight	2.746 kg
Unit Type of Package 3	P12
Number of Units in Package 3	280

Package 3 Height	71.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	89.500 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes