



### Main

|                                    |  |
|------------------------------------|--|
| Range                              | PrismaSeT  |
| Range of product                   | PrismaSeT P  |
| Product or component type          | Connection transfer assembly                                   |
| Product name                       | PrismaSeT PrismaSeT P enclosure                                |
| Accessory / separate part category | Current distribution accessory                                 |
| Standards                          | IEC 61439-2, inside enclosure<br>IEC 61439-1, inside enclosure |
| Product certifications             | ASTA   |

### Complementary

|                                |  |
|--------------------------------|--|
| Cubicle-device connection      | Flat busbar  |
| Poles description              | 4P   |
| Installation description       | Cubicle - width 650 mm   |
| Installed device               | ComPact: fixed NSX400 without earth leakage protection - control: toggle horizontal installation<br>ComPact: fixed NSX630 without earth leakage protection - control: toggle horizontal installation |
| [Ie] rated operational current | 630 A  |
| Busbar cross section           | 32 x 6 mm  |
| Height                         | 250 mm   |
| Net weight                     | 7.18 kg  |
| Quantity per set               | Set of 1   |
| Functional unit                | 650 mm 400 mm PrismaSeT P cubicle ComPact NSX400 without fixed toggle horizontal 4P 1 direct 5<br>650 mm 400 mm PrismaSeT P cubicle ComPact NSX630 without fixed toggle horizontal 4P 1 direct 5     |

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 16.0 cm  |
| Package 1 Width              | 27.5 cm  |
| Package 1 Length             | 40.0 cm  |
| Package 1 Weight             | 7.071 kg |
| Unit Type of Package 2       | P12      |
| Number of Units in Package 2 | 9        |
| Package 2 Height             | 29.0 cm  |
| Package 2 Width              | 80.0 cm  |
| Package 2 Length             | 120.0 cm |
| Package 2 Weight             | 75.0 kg  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| RoHS exemption information | <a href="#">Yes</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |
| Circularity Profile        | No need of specific recycling operations   |