
LVS04473

Connection, Linergy LGY, for NS, 3P, 1000A, horizontal fixed





| Main | |
|------------------------------------|--|
| Range | PrismaSeT |
| Range of product | PrismaSeT P |
| Product or component type | Connection |
| Product name | PrismaSeT PrismaSeT P enclosure |
| Accessory / separate part category | Current distribution accessory |
| Standards | IEC 61439-2, inside enclosure IEC 61439-1, inside enclosure |
| Product certifications | ASTA |

Complementary

| Cubicle-device connection | Linergy busbar |
|--------------------------------|---|
| Poles description | 3P |
| Installation description | Cubicle - width 650 mm Cubicle + duct - width 650 mm |
| Installed device | ComPact: fixed NS630b1000 - control: toggle horizontal installation ComPact: fixed NS630b1000 - control: direct front rotary handle horizontal installation |
| [le] rated operational current | 1000 A |
| Busbar cross section | 50 x 8 mm |
| Net weight | 4.66 kg |
| Quantity per set | Set of 1 |
| Functional unit | 650 mm 800 mm PrismaSeT P cubicle ComPact NS630b1000 fixed toggle horizontal 3P 1 rear connection 7 650 mm 800 mm PrismaSeT P cubicle ComPact NS630b1000 fixed direct front rotary handle horizontal 3P 1 rear connection 7 650 mm 400 mm PrismaSeT P cubicle + duct ComPact NS630b1000 fixed toggle horizontal 3P 1 front connection 7 650 mm 400 mm PrismaSeT P cubicle + duct ComPact NS630b1000 fixed toggle horizontal 3P 1 connection transfer assembly 8 650 mm 400 mm PrismaSeT P cubicle + duct ComPact NS630b1000 fixed direct front rotary handle horizontal 3P 1 front connection 7 650 mm 400 mm PrismaSeT P cubicle + duct ComPact NS630b1000 fixed direct front rotary handle horizontal 3P 1 connection transfer assembly 8 |

Packing Units

| · coming of the | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.5 cm |
| Package 1 Width | 14.0 cm |
| Package 1 Length | 39.0 cm |
| Package 1 Weight | 4.623 kg |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 64 |
| Package 2 Height | 36.0 cm |
| Package 2 Width | 80.0 cm |
| Package 2 Length | 120.0 cm |
| Package 2 Weight | 307.0 kg |
| | |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|--|
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EV EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | €Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| PVC free | Yes |
| | |