



## Main

Range	Lineryg
Range of product	Lineryg
Product or component type	Profile busbar
Product name	Lineryg LGY
Range compatibility	PrismaSeT PrismaSeT P enclosure
Busbar description	Lineryg
Quantity per set	Set of 1

## Complementary

Installation direction	Vertical, operating position: rear Vertical, operating position: lateral
Installation description	Cubicle - width 650 mm Cubicle - width 650 + 150 mm
[Ui] rated insulation voltage	1000 V
[Uimp] rated impulse withstand voltage	12 kV (degree of pollution: 3)
[Ie] rated operational current	1000 A
[Icw] rated short-time withstand current	25 kA (1 s) for 3 supports (rear position) 30 kA (1 s) for 4 supports (rear position) 40 kA (1 s) for 3 supports (lateral position) 40 kA (1 s) for 5 supports (rear position)
Permissible current	1040 A at 35 °C: <= IP31 950 A at 35 °C: > IP31
Busbar cross section	32.5 x 42.5 mm
Length	1670 mm
Net weight	2.28 kg
Colour	Natural
Type of busbar connection	Single t-slot
Connection pitch	Free connection position

## Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.750 cm
Package 1 Width	4.750 cm
Package 1 Length	177.000 cm
Package 1 Weight	2.154 kg
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Height	7.500 cm

Package 2 Width	9.500 cm
Package 2 Length	177.000 cm
Package 2 Weight	8.617 kg
Unit Type of Package 3	P2M
Number of Units in Package 3	80
Package 3 Height	29.000 cm
Package 3 Width	120.000 cm
Package 3 Length	200.000 cm
Package 3 Weight	190.560 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product