



## Main

Range	Linergy
Range of product	Linergy
Product or component type	Profile busbar
Product name	Linergy LGYE
Range compatibility	PrismaSeT PrismaSeT P enclosure
Busbar description	Linergy
Quantity per set	Set of 1

## Complementary

Installation direction	Vertical, operating position: lateral Horizontal, operating position: top Horizontal, operating position: bottom
Installation description	Cubicle - width 650 mm Cubicle - width 650 + 150 mm Cubicle duct - width 300 mm
[Ui] rated insulation voltage	1000 V
[Uimp] rated impulse withstand voltage	12 kV (degree of pollution: 3)
[Ie] rated operational current	4000 A
[Icw] rated short-time withstand current	60 KA (1 s) for 2 supports (horizontal position) 85 KA (1 s) for 3 supports (horizontal position) 85 KA (1 s) for 7 supports (lateral position) 100 KA (1 s) for 4 supports (horizontal position) 100 KA (1 s) for 9 supports (lateral position) 60 KA (1 s) for 3 supports (lateral position) 75 kA (1 s) for 5 supports (lateral position)
Permissible current	3620 A at 35 °C: <= IP31 3350 A at 35 °C: > IP31
Length	1625 mm
Colour	Natural
Type of busbar connection	Double t-slot
Connection pitch	Free connection position

## Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	15.8 cm
Package 1 Length	177.5 cm
Package 1 Weight	18.079 kg
Unit Type of Package 2	PAL

Number of Units in Package 2	18
Package 2 Height	27.0 cm
Package 2 Width	120.0 cm
Package 2 Length	202.0 cm
Package 2 Weight	349.0 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product