
# LVS04516 DRILLED VERTICAL FLAT BAR LINERGY BS 60X5 L1675





Main	
Range	Linergy
Range of product	Linergy
Product or component type	Busbar
Product name	Linergy BS
Range compatibility	PrismaSeT PrismaSeT P enclosure
Busbar description	Flat bar
Quantity per set	Set of 1

#### Complementary

Installation direction	Vertical, operating position: rear
	Vertical, operating position: lateral
Installation description	Cubicle - width 650 mm
	Cubicle - width 650 + 150 mm
[le] rated operational current	800 A at 35 °C
[lcw] rated short-time withstand current	15 KA (1 s) for 3 supports (lateral position)
	30 KA (1 s) for 5 supports (lateral position)
	40 KA (1 s) for 7 supports (lateral position)
	15 KA (1 s) for 3 supports (rear position)
	30 KA (1 s) for 5 supports (rear position)
	40 kA (1 s) for 7 supports (rear position)
Permissible current	800 A at 35 °C: <= IP31
	750 A at 35 °C: > IP31
Busbar cross section	60 x 5 mm
Length	1675 mm
Width	60 mm
Depth	5 mm
Net weight	4.54 kg
Colour	Natural
Type of busbar connection	Ø 10 mm drilled hole
Connection pitch	Connection each 25 mm

#### Environment

Standards	IEC 61439-1 IEC 61439-2	
Product certifications	ASTA	

### Packing Units

PCE	
1	
1.500 cm	
14.500 cm	
179.500 cm	
4.446 kg	
PAL	
	1 1.500 cm 14.500 cm 179.500 cm 4.446 kg

Number of Units in Package 2	80
Package 2 Height	34.000 cm
Package 2 Width	120.000 cm
Package 2 Length	202.000 cm
Package 2 Weight	374.000 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant <sup>☑</sup> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<sup>™</sup> China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product