



Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Interface and connection Canalis
Product name	PrismaSeT PrismaSeT P enclosure Canalis Canalis KT busbar trunking Masterpact MasterPact NW circuit breaker
Accessory / separate part category	Interface accessory
Standards	IEC 61439-2, inside enclosure IEC 61439-1, inside enclosure
Product certifications	ASTA

Complementary

Cubicle-device connection	KT with Canalis
Poles description	4P
Installation description	Cubicle - width 650 mm
Cubicle depth	600 mm: front 600 + 400 mm: rear
Installed device	Masterpact: drawout NW32 - control: toggle vertical installation Masterpact: fixed NW32 - control: toggle vertical installation
[Ie] rated operational current	3200 A
Height	350 mm
Width	575 mm
Depth	450 mm
Net weight	70 kg
Quantity per set	Set of 1
Functional unit	650 mm 600 mm PrismaSeT P cubicle Masterpact NW32 drawout toggle vertical 4P 1 front connection on Canalis 28 650 mm 1000 mm PrismaSeT P cubicle Masterpact NW32 drawout toggle vertical 4P 1 rear connection on Canalis 17 650 mm 600 mm PrismaSeT P cubicle Masterpact NW32 fixed toggle vertical 4P 1 front connection on Canalis 28 650 mm 1000 mm PrismaSeT P cubicle Masterpact NW32 fixed toggle vertical 4P 1 rear connection on Canalis 16

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43.000 cm
Package 1 Width	41.500 cm
Package 1 Length	61.500 cm
Package 1 Weight	64.000 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations