



**Main**

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Interface and connection Canalis
Product name	PrismaSeT PrismaSeT P enclosure Canalis Canalís KT busbar trunking Masterpact MasterPact NW circuit breaker
Accessory / separate part category	Interface accessory
Standards	IEC 61439-2, inside enclosure IEC 61439-1, inside enclosure
Product certifications	ASTA

**Complementary**

Cubicle-device connection	KT with Canalis
Poles description	3P
Location of connection	Upstream
Installation description	Cubicle 4000A - width 650 mm
Cubicle depth	600 + 400 mm: rear
Installed device	Masterpact: NW40 vertical installation - rear connection
[Ie] rated operational current	4000 A
Height	350 mm
Width	575 mm
Depth	450 mm
Quantity per set	Set of 1

**Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	45.000 cm
Package 1 Width	40.000 cm
Package 1 Length	61.000 cm
Package 1 Weight	84.500 kg

**Offer Sustainability**

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
RoHS exemption information	<input checked="" type="checkbox"/> Yes
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
Circularity Profile	No need of specific recycling operations