



### Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Door
Range compatibility	PrismaSeT PrismaSeT P duct
Provided equipment	Door Other keylock and insert to be ordered separately 4 hinge Black handle with lock for 405 key Polyurethane joint
Enclosure mounting	Floor-standing
Type of door	Plain
IP degree of protection	IP55

### Complementary

Installation description	Duct - width 300 mm
Door opening side	Reversible
Number of locks	3
Door opening angle	120 °
Number of vertical modules [50 mm]	36
Enclosure material	Treated sheet steel
Quantity per set	Set of 1
Height	1925 mm
Width	300 mm
Depth	30 mm
Net weight	14.76 kg
Surface finish	Matt Textured
Colour	White (RAL 9003)

### Environment

IK degree of protection	IK10 conforming to EN/IEC 62262
Standards	IEC 61439-2 IEC 61439-1
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.000 cm
Package 1 Width	36.000 cm
Package 1 Length	197.000 cm
Package 1 Weight	15.030 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	30
Package 2 Height	83.000 cm
Package 2 Width	120.000 cm

Package 2 Length	202.000 cm
Package 2 Weight	477.000 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations