



## Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Door
Range compatibility	PrismaSeT PrismaSeT P cubicle duct
Provided equipment	Door Other keylock and insert to be ordered separately 2 hinge Black handle with lock for 405 key
Enclosure mounting	Floor-standing
Type of door	HSI cut-out
IP degree of protection	IP30

## Complementary

Installation description	Cubicle duct - width 400 mm
Door opening side	Reversible
Number of locks	2
Door opening angle	120 °
Number of vertical modules [50 mm]	36
Additional information	Can be equipped with front plates for 72 x 72 mm or 96 x 96 mm instruments
Quantity per set	Set of 1
Height	1925 mm
Width	400 mm
Net weight	10.4 kg
Surface finish	Textured Matt
Colour	White (RAL 9003)

## Environment

IK degree of protection	IK08 conforming to EN/IEC 62262
Standards	IEC 61439-1 IEC 61439-2
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	46.5 cm
Package 1 Length	198.0 cm
Package 1 Weight	12.2 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	10
Package 2 Height	51.0 cm
Package 2 Width	120.0 cm

Package 2 Length	202.0 cm
Package 2 Weight	142.0 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations