



Main

Range	PrismaSeT
Product name	XS
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Enclosure mounting	Surface

Complementary

Width	Total: 550 mm
Height	Total: 450 mm
Depth	Total : 168 mm
Internal depth	155 mm
Number of 18 mm modules per row	24
Number of horizontal rows	2
Total number of 18 mm modules	48
9 mm pitches	96
Electrical insulation class	Class II
Provided equipment	2 identification label 2 label protector 1 terminal block 1 blanking plate strip 1 door 2 DIN rail 2 cable fixing hardware 1 back plate
Type of front plate	Modular
Door type	Transparent
Type of rail	Symmetrical DIN
Mounting plate description	Without mounting plate
Removable parts	DIN rail
Power dissipation in W	67 W
[In] rated current	125 A
[Ui] rated insulation voltage	400 V
Cable entry	Cable or tube Cut-out plates Trunking Removable plates
Number of terminal blocks	1 earth with 24.0 outgoers
Distribution block outgoers	3 x 25 mm ² + 21 x 4 mm ² for earth
Connections - terminals	Screw connection (earth) , 3.0 x 6...25 mm ² Push-in (earth) , 21.0 x 1.5...4 mm ² (flexible) Push-in (earth) , 21.0 x 6 mm ² (rigid or stranded)
Locking options description	Keylock option

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Enclosure material	Back part: metal Enclosure: technoplastic Front plate: technoplastic Door: glass
Net weight	10.270 kg
Colour	Enclosure: white (RAL 9003) Front plate: white (RAL 9003) Door: colourless
Market segment	Residential Small buildings
Targeted country	Belgium

Environment

Fire resistance	Enclosure: 650 °C conforming to IEC 60695-2-11 Front plate: 650 °C conforming to IEC 60695-2-11
IP degree of protection	IP40 with closed door
IK degree of protection	IK09 with closed door
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C
Standards	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3
Quality labels	IMQ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.5 cm
Package 1 Width	54 cm
Package 1 Length	64 cm
Package 1 Weight	10.2 kg
Unit Type of Package 2	P12
Number of Units in Package 2	10
Package 2 Height	124 cm
Package 2 Width	80 cm
Package 2 Length	120 cm
Package 2 Weight	112 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product