LX1G3RLSEA

Control module, TeSys Giga, 200-500V AC/DC, for LC1G265-330/3P advanced version





Main

	T.O.:
Range	TeSys
Product or component	Contactor coil
type	
Device short name	LX1G
Poles description	3P
Range compatibility	TeSys G LX1G contactor coil
Product compatibility	LC1G265330
[Uc] control circuit	200500 V AC/DC 50/60 Hz
voltage	
Operating time	2035 ms opening
	4055 ms closing
Mechanical durability	5 Mcycles
Maximum operating rate	600 cyc/mn 60 °C

Complementary

Coil technology	Built-in bidirectional peak limiting
Control circuit voltage limits	Operational: 0.81.1 Uc (at 60 °C) Drop-out: 00.45 Uc (at 60 °C)
Connections - terminals	Control circuit: push-in termination 1 cable(s) 0.22.5 mm² solid stranded without cable end sleeve AWG 26AWG 12 Control circuit: push-in termination 1 cable(s) 0.252.5 mm² flexible with cable end sleeve AWG 24AWG 14 Control circuit: push-in termination 2 cable(s) 0.51.0 mm² rigid or stranded with cable end sleeve AWG 20AWG 18
Inrush power in VA	375 VA at 480 V AC, 60 Hz
Inrush power in W	270.0 W DC
Hold-in power consumption in VA	14.6 VA at 480 V AC, 60 Hz
Hold-in power consumption in W	4.4 W for DC network

Environment

Environment	
IP degree of protection	IP20 conforming to IEC 60529
Operating altitude	3000 m without derating
	5000 m with derating factor
Electromagnetic compatibility	EMC immunity conforming to IEC 60947-4-1
	Emission tests criteria A conforming to IEC 60947-4-1
	Immunity to radiated radio-electrical interference - test level: 20 V/m conforming to EN/IEC 61000-4-3
	Voltage dips and interruptions immunity test conforming to SEMI F47
Standards	EN/IEC 60947-4-1
	UL 60947-4-1A
	CSA C22.2 No 60947-4-1
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-2560 °C
Ambient air temperature for storage	-6080 °C
Permissible ambient air temperature around the	-4070 °C at Uc
device	
Height	167.0 mm
Width	140.0 mm
Depth	93.0 mm
Quantity per set	1

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.0 cm
Package 1 Width	24.0 cm
Package 1 Length	22.0 cm
Package 1 Weight	2.0 kg
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.6 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	[™] China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Product data sheet Dimensions Drawings

LX1G3RLSEA

LX1G3RLSEA

Product data sheet Performance Curves

LX1G3RLSEA