



Main

Range of product	PacDrive 3
Device short name	LXM 62
Product or component type	Single drive

Complementary

Product compatibility	Servo motor SH3 (140 mm, 4 motor stacks)optimized in terms of torque and speed Servo motor SH3 (205 mm, 1 motor stacks)optimized in terms of torque and speed Servo motor SH3 (205 mm, 2 motor stacks)optimized in terms of torque and speed Servo motor SH3 (205 mm, 3 motor stacks)optimized in terms of torque and speed Servo motor MH3 (140 mm, 2 motor stacks)optimized in terms of torque and speed Servo motor MH3 (140 mm, 3 motor stacks)optimized in terms of torque and speed Servo motor MH3 (190 mm, 1 motor stacks)optimized in terms of torque and speed Servo motor MH3 (190 mm, 2 motor stacks)optimized in terms of torque and speed Servo motor MH3 (190 mm, 3 motor stacks)optimized in terms of torque and speed Servo motor SHS
Network number of phases	Three phase
[Us] rated supply voltage (through power supply module)	400 V (- 10...10 %) for three phase 230 V (- 10...10 %) for three phase 230 V (- 10...10 %) for single phase
Supply frequency	50/60 Hz - 5...5 %
Continuous output current	50 A at 4 kHz
Output current 3s peak	130 A at 4 kHz
Continuous power	24.7 kW
Nominal power	24.7 kW
Switching frequency	8 kHz
Overvoltage category	III
Electrical connection	Terminal, clamping capacity: 0.2...15 mm <sup>2</sup> , AWG 24...AWG 16 (CN4) Terminal, clamping capacity: 0.5...16 mm <sup>2</sup> , AWG 20...AWG 6 (CN5) Terminal, clamping capacity: 0.75...16 mm <sup>2</sup> , AWG 18...AWG 6 (CN6) Terminal, clamping capacity: 0.2...6 mm <sup>2</sup> , AWG 24...AWG 10 (CN7)
Tightening torque	CN1: 2.5 N.m
Number of inputs	2 digital 2 touch probe
Discrete input voltage	24 V DC for - 20...25 %
Number of outputs	2 digital
Discrete output voltage	24 V DC

Safety function	STO (safe torque off) SS1 (safe stop 1) SS2 (safe stop 2) SOS (safe operating stop) SMS (safe maximum speed) SLS (safe limited speed) SDI (safe direction indication)
Communication interface	SERCOS III, integrated
Depth	270 mm
Height	310 mm
Width	89.5 mm
Net weight	6.8 kg

## Environment

Standards	IEC 61800-3 ISO 13849-1 ISO 13849-2 CSA C22.2 No 14 UL 508C IEC 61800-5-2 IEC 61800-5-1 IEC 62061 IEC 62061 IEC 61508
Product certifications	EAC[RETURN]CE[RETURN]UL[RETURN]TÜV[RETURN]CSA
IP degree of protection	IP20 conforming to IEC 60529
Vibration resistance	10 m/s <sup>2</sup> conforming to IEC 60721-3-3
Shock resistance	100 m/s <sup>2</sup> conforming to IEC 60721-3-3
Pollution degree	2 conforming to IEC 61800-5-2
Environmental characteristic	3K3 conforming to IEC 60721-3-3
Relative humidity	5...85 %
Ambient air temperature for operation	5...55 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.2 cm
Package 1 Width	32.5 cm
Package 1 Length	42.5 cm
Package 1 Weight	3.91 kg
Unit Type of Package 2	S06
Number of Units in Package 2	6
Package 2 Height	75.0 cm
Package 2 Width	60.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	36.46 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> <a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<input checked="" type="checkbox"/> <a href="#">China RoHS Declaration</a>
RoHS exemption information	<input checked="" type="checkbox"/> Yes
Environmental Disclosure	<input checked="" type="checkbox"/> <a href="#">Product Environmental Profile</a>
Circularity Profile	<input checked="" type="checkbox"/> <a href="#">End Of Life Information</a>
PVC free	Yes