



Main

Range of product	Lexium Cobot
Product or component type	Collaborative robot
Maximum payload	3 kg
Operating radius	626 mm
Positioning accuracy	+/- 0.02 mm
Degree of freedom	6
Programming	Graphical drag & drop
Teach-in device	Ipad ios app Android app

Complementary

Maximum speed	180°/S joint 1 +/- 360° 180°/S joint 2 -85, +265° 180°/S joint 3 +/- 175° 220°/S joint 4 -85, +265° 220°/S joint 5 +/- 360° 220°/s joint 6 +/- 360°
Rated voltage	24 V
Digital input number	2
Digital output number	2
Analogue input number	1
Maximum power consumption in W	150 W
Mounting position	Any position
Screw type	M8
Standards	GB 11291.1:2011 EN/ISO 10218-1:2011 EN 60204-1:2018 EN/ISO 12100:2010 EN/ISO 13849-1:2015 EN 61000-6-2:2005 EN 61000-6-4:2007+A1:2011 ISO 13849-1:2015 ISO 13849-2:2012 ISO 14644-1 ISO 9001:2015 UL 1740 ANSI/RIA R15.06 CAN/CSA Z434 NFPA 79 CAN/CSA C22.2 No. 24 REACH RoHS
Marking	CE KC TÜV
Material	Aluminium
Base diameter	129 mm
Cable length	6 m
Net weight	12 kg

Environmental

IP degree of protection	IP54
Ambient air temperature for operation	0...50 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	37 cm
Package 1 Width	42 cm
Package 1 Length	49 cm
Package 1 Weight	14.6 kg
Unit Type of Package 2	P06
Number of Units in Package 2	2
Package 2 Height	75 cm
Package 2 Width	60 cm
Package 2 Length	80 cm
Package 2 Weight	37.7 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile