



Main

Range of product	Lexium Cobot
Product or component type	Collaborative robot
Maximum payload	5 kg
Operating radius	954 mm
Positioning accuracy	+/- 0.02 mm
Degree of freedom	6
Programming	Graphical drag & drop
Teach-in device	Ipad ios app Android app

Complementary

Maximum speed	180°/S joint 1 +/- 360° 180°/S joint 2 -85, +265° 180°/S joint 3 +/- 175° 180°/S joint 4 -85, +265° 180°/S joint 5 +/- 360° 180°/s joint 6 +/- 360°
Rated voltage	24 V
Digital input number	2
Digital output number	2
Analogue input number	1
Maximum power consumption in W	350 W
Mounting position	Any position
Screw type	M8
Standards	GB 11291.1:2011 EN/ISO 10218-1:2011 EN 60204-1:2018 EN/ISO 12100:2010 EN/ISO 13849-1:2015 EN 61000-6-2:2005 EN 61000-6-4:2007+A1:2011 ISO 13849-1:2015 ISO 13849-2:2012 ISO 14644-1 ISO 9001:2015 UL 1740 ANSI/RIA R15.06 CAN/CSA Z434 NFPA 79 CAN/CSA C22.2 No. 24 REACH RoHS
Marking	CE KC TÜV
Material	Aluminium
Base diameter	158 mm
Cable length	6 m
Net weight	23 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

IP degree of protection	IP54
Ambient air temperature for operation	0...50 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	41.500 cm
Package 1 Width	44.500 cm
Package 1 Length	65.000 cm
Package 1 Weight	25.478 kg
Unit Type of Package 2	P12
Number of Units in Package 2	4
Package 2 Height	105.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	115.000 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile