



Main

Product or component type	Valve
Valve type	Shoe
Valve product series	MB
Medium compatibility	Glycol 25 % Water
Valve configuration	3-Way
Valve connection type	Rp Internal
Body size	20 mm (3/4 in)
Pipe size	3/4 in
Flow characteristic	Equal percentage
Flow coefficient	4.62 cv 4 kvs
Pressure class	PN10
Operating fluid temperature	2...120 °C
Valve Rotation	90 °
Control valve rangeability	50:1
Seat leakage	Port A: Class II (0.5 %)
Stem movement	Rotary
Trim material	Brass
Body material	Forged brass
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	10.0 cm
Package 1 Length	12.0 cm
Package 1 Weight	841.0 g

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.