

MB3-24F-T3

SpaceLogic MB3 Ball Valve Actuator, 3 Wire
Floating, Non-Spring Return, 24VAC, 3Nm,
Rotary, IP31



Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	MB3
Actuator model	MB3-24F T31 T3
Product destination	Ball valves
Actuator	Rotary
Control type	Electrically operated
Rated supply voltage	24 V AC
Transformer rated power in VA	10 VA
Power consumption in W	2.5 W
Power consumption in VA	2.5 VA AC
Power loss return	Non-spring return
Control signal	Floating
Electrical insulation class	Class III
Tightening torque	26 lb.in 2.9 N.m
Position indicator	Green push stem with color markers
Additional features	Cable gland fitted for 5-9mm wire OD
Conduit connection	M20
IP degree of protection	IP31
Ambient air temperature for operation	0...60 °C
Relative humidity	5...95 % non-condensing
Ambient air temperature for storage	-40...76 °C
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.1 cm
Package 1 Width	10.7 cm
Package 1 Length	17.0 cm
Package 1 Weight	900.0 g

Offer Sustainability

EU RoHS Directive	Not compliant
Environmental Disclosure	 Product Environmental Profile