



Main

Range	PowerLogic
Product or component type	Remote display
Device application	Human-machine dialogue application
Range compatibility	PowerLogic PowerLogic ION9000
Display type	LCD touch screen

Complementary

Display colour	Color
Display resolution	800 x 480 pixels
Display size	7 inch
Information displayed	Energy consumption Voltage Power Harmonic distortion Frequency Current System alarm I/O status
Messages display capacity	Graphic objects (bargraph, button, light...)
Local signalling	Status: LED (green) Alarm: LED (red)
Control type	1 x push-button Touch screen
Connector type	RJ45
Provided equipment	Mounting hardware
Mounting mode	Flush-mounted
Mounting support	Framework remote display
Width	197 mm
Height	175 mm
Projecting depth	27.5 mm
Net weight	300 g

Environment

IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK08
Relative humidity	5...95 %
Operating altitude	0...3000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C
Product certifications	IEC[RETURN]IEEE

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.0 cm
Package 1 Width	24.0 cm
Package 1 Length	26.0 cm
Package 1 Weight	1.6 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins