

MF40-24F

Act: Elec, 3P Float, SR, 24 VAC/VDC, 40 Nm,
Rotary, SPDT, IP54




Main

| | |
|---------------------------------------|---------------------------------------|
| Product or component type | Actuator |
| Actuator type | Electric |
| Actuator product series | MF40 |
| Actuator model | MF40-24F T54 00 |
| Product destination | Butterfly valves |
| Actuator | Rotary |
| Control type | Electrically operated |
| Switch function | 2 SPDT (optional) |
| Rated supply voltage | 24 V AC/DC |
| Power consumption in W | 4 W |
| Power consumption in VA | 6 VA AC |
| Hold-in power consumption in W | 2 W |
| Power loss return | Stay in place |
| Control signal | 2-position (on/off) Floating |
| Electrical insulation class | Class III |
| Tightening torque | 354 lb.in 40 N.m |
| Position indicator | Stroke indicator on bracket |
| Leads and connections | Terminal block |
| IP degree of protection | IP54 |
| Ambient air temperature for operation | 0...50 °C |
| Targeted region | Europe Asia Pacific. Australia. |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 11.2 cm |
| Package 1 Width | 17.2 cm |
| Package 1 Length | 23.7 cm |
| Package 1 Weight | 2.248 kg |

Offer Sustainability

| | |
|----------------------------|---|
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |