

MF40ER-24M

MF40-ER Butterfly Valve Actuator, Modulating,
2-10VDC, 24Vac/dc, 40Nm, Electronic Return,
IP54



Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	MF40ER
Actuator model	MF40ER-24M
Product destination	Butterfly valves
Actuator	Rotary
Control type	Electrically operated
Feedback signal	2...10 V DC
Power consumption in W	11 W
Hold-in power consumption in W	3 W
Power loss return	Spring return
Control signal	Proportional/modulating
Electrical insulation class	Class II
Tightening torque	354 lb.in 40 N.m
Position indicator	Stroke indicator on bracket
Lead length	1.5 m
IP degree of protection	IP54
Material	Reinforced teflon: seal EPDM: O-rings
Ambient air temperature for operation	0...50 °C
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.0 cm
Package 1 Width	19.0 cm
Package 1 Length	29.0 cm
Package 1 Weight	2.81 kg

Offer Sustainability

EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations