

MF40ER-24T

MF40-E0R Butterfly Valve Actuator, Electronic Return, On/Off or 3 position floating, 24Vac/dc, 40Nm, IP54





Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	MF40ER
Actuator model	MF40ER-24T
Product destination	Butterfly valves
Actuator	Rotary
Control type	Electrically operated
Power consumption in W	11 W
Hold-in power consumption in W	3 W
Power loss return	Spring return
Control signal	2-position (on/off) Floating
Electrical insulation class	Class II
Tightening torque	354 lb.in 40 N.m
Position indicator	Stroke indicator on bracket
Lead length	1.5 m
IP degree of protection	IP54
Material	Reinforced teflon: seal EPDM: O-rings
Ambient air temperature for operation	0...50 °C
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.0 cm
Package 1 Width	19.5 cm
Package 1 Length	29.5 cm
Package 1 Weight	2.8 kg

Offer Sustainability

EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes