

MF68-24M

MF68 Butterfly Valve Actuator, Modulating, 0-10Vdc or 2-10Vdc, Non-Spring Return, 24Vac, 68Nm, SPDT Aux Switch + Integrated Heater, IP65




Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	MF68
Product destination	Butterfly valves
Actuator	Rotary
Switch function	2 SPDT
Rated supply voltage	24 V AC
Feedback signal	0...10 V DC
Power loss return	Non-spring return
Control signal	Proportional/modulating
Tightening torque	601 lb.in 68 N.m
Leads and connections	Terminal block
IP degree of protection	IP65
Material	Reinforced teflon: seal EPDM: O-rings
Ambient air temperature for operation	-29...65 °C
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-40...65 °C
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.0 cm
Package 1 Width	29.0 cm
Package 1 Length	32.0 cm
Package 1 Weight	6.0 kg

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.