

MF700-230F

MF700 Butterfly Valve Actuator, On/Off or
3 Position Floating Control, Non-Spring
Return, 230Vac, 700Nm, SPDT Aux Switch +
Integrated Heater, IP65

Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	MF700
Product destination	Butterfly valves
Actuator	Rotary
Control type	Electrically operated
Switch function	2 SPDT
Rated supply voltage	230 V AC
Feedback signal	0...10 V DC
Hold-in power consumption in W	5 W
Hold-in power consumption in VA	258 VA AC
Power loss return	Non-spring return
Control signal	2-position (on/off) Floating
Tightening torque	6505 lb.in 735 N.m
Additional features	Heater
Leads and connections	Terminal block
Spring return timing	36 s
IP degree of protection	IP65
Material	Reinforced teflon: seal EPDM: O-rings
Duty cycle	25 %
Ambient air temperature for operation	-25...65 °C
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-40...65 °C
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	38.0 cm
Package 1 Width	36.0 cm
Package 1 Length	41.0 cm
Package 1 Weight	22.25 kg

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes