



Main

Range of product	SpaceLogic KNX
Product or component type	Dimming actuator
Operating mode	KNX bus system
Bus type	KNX

Complementary

Mounting support	Flush
[Ue] rated operational voltage	230 V
Network frequency	50/60 Hz
Current consumption	5...18 mA for bus
Input type	3 x binary AC
Number of outputs	1
Load type	Incandescent lamps: 20...230 W at 230 V AC High voltage halogen lamp: 20...210 W at 230 V AC LV halogen lamps: 20...210 W at 230 V AC (inductive transformer) LV halogen lamps: 20...210 W at 230 V AC (capacitive transformer) LED lamp: 1...200 W at 230 V AC (phase cut-off) LED lamp: 1...32 W at 230 V AC (phase cut-on)
Maximum cable length	10 m for input
Width	48 mm
Height	50 mm
Depth	28 mm

Environment

IP degree of protection	IP20
Ambient air temperature for operation	-5...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	7.6 cm
Package 1 Length	7.6 cm
Package 1 Weight	106.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	60
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	6.875 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------