



Main

Range of product	KNX
Product or component type	Binary input
Bus type	KNX

Complementary

Total number of 18 mm modules	4
Wiring device mounting	DIN rail
[Ue] rated operational voltage	24 V AC/DC 50 Hz
Number of inputs	8
Input type	Binary
Local signalling	LED

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.200 cm
Package 1 Width	13.400 cm
Package 1 Length	15.900 cm
Package 1 Weight	232.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	19.800 cm
Package 2 Width	30.900 cm
Package 2 Length	40.400 cm
Package 2 Weight	2.700 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months