



Main

Range of product	KNX
Product or component type	Binary input
Bus type	KNX

Complementary

Total number of 18 mm modules	2.5
Wiring device mounting	DIN rail
[Ue] rated operational voltage	24 V AC/DC 50 Hz
Number of inputs	4
Input type	Binary
Local signalling	LED

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.100 cm
Package 1 Width	7.700 cm
Package 1 Length	9.700 cm
Package 1 Weight	152.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	30
Package 2 Height	19.600 cm
Package 2 Width	30.800 cm
Package 2 Length	41.600 cm
Package 2 Weight	4.720 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration

RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------