



Main

| | |
|---------------------------|--------------|
| Range of product | KNX |
| Product or component type | Binary input |
| Bus type | KNX |

Complementary

| | |
|--------------------------------|----------------|
| Total number of 18 mm modules | 2.5 |
| Wiring device mounting | DIN rail |
| [Ue] rated operational voltage | 230 V AC 50 Hz |
| Number of inputs | 4 |
| Input type | Binary |
| Local signalling | LED |

Environment

| | |
|-------------------------|------|
| IP degree of protection | IP20 |
|-------------------------|------|

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.7 cm |
| Package 1 Width | 7.3 cm |
| Package 1 Length | 9.6 cm |
| Package 1 Weight | 156.0 g |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 30 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 5.17 kg |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |

| | |
|----------------------------|---|
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|