



Main

Range of product	KNX
Product or component type	Control unit 0-10 V
Operating mode	KNX bus system Manual
Bus type	KNX

Complementary

Total number of 18 mm modules	4
Mounting support	DIN rail
[Ue] rated operational voltage	100...240 V AC 50...60 Hz
Input current	0.12...100 mA
Analogue output type	Voltage
Analogue output range	1...10 V
Number of outputs	3
[In] rated current	16 A
Load type	Incandescent lamps: ≤ 1600 W, 100 V AC Incandescent lamps: ≤ 3600 W, 230 V AC Incandescent lamps: ≤ 3840 W, 240 V AC Halogen lamps: ≤ 1086 W, 100 V AC Halogen lamps: ≤ 2500 W, 230 V AC Halogen lamps: ≤ 2608 W, 240 V AC Parallel compensated fluorescent lamp: ≤ 1086 VA, 100 V AC Parallel compensated fluorescent lamp: ≤ 2500 VA, 230 V AC Parallel compensated fluorescent lamp: ≤ 2608 VA, 240 V AC Capacitive: , 16 A, 200 μF, 100...240 V AC

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.200 cm
Package 1 Width	12.600 cm
Package 1 Length	15.800 cm
Package 1 Weight	340.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	10
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.580 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------