



Main

Range of product	KNX
Product or component type	Switch actuator
Operating mode	Manual
Bus type	KNX
Modular device additional info	Connectable with different phases
Number of contacts	8

Complementary

Total number of 18 mm modules	8
Mounting support	DIN rail
[Ue] rated operational voltage	100...240 V
Network frequency	50...60 Hz
[In] rated current	16 A
Load type	Incandescent lamps: <= 3600 W, 230 V AC Halogen lamps: <= 2500 W, 230 V AC Incandescent lamps: <= 1600 W, 100 V AC Incandescent lamps: <= 3840 W, 240 V AC Halogen lamps: <= 1086 W, 100 V AC Halogen lamps: <= 2608 W, 240 V AC Parallel compensated fluorescent lamp: <= 1086 VA, 100 V AC Parallel compensated fluorescent lamp: <= 2500 VA, 230 V AC Parallel compensated fluorescent lamp: <= 2608 VA, 240 V AC Capacitive: , 16 A, 200 µF, 100...240 V AC

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.300 cm
Package 1 Width	13.000 cm
Package 1 Length	28.000 cm
Package 1 Weight	626.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.148 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------