



Main

Range of product	KNX
Product or component type	Blind actuator
Operating mode	KNX bus system Manual
Bus type	KNX

Complementary

Total number of 18 mm modules	4
Mounting support	DIN rail
[Ue] rated operational voltage	24 V DC
[In] rated current	6 A
Number of outputs	4
Load type	Motor: , 24 V DC
Local signalling	LED

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.200 cm
Package 1 Width	13.400 cm
Package 1 Length	15.900 cm
Package 1 Weight	374.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	19.700 cm
Package 2 Width	30.500 cm
Package 2 Length	41.000 cm
Package 2 Weight	4.126 kg

Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	RECh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration

RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------