




Main

Range of product	KNX
Product or component type	Power supply
Network type	AC

Complementary

Condition of use	Other device KNX device
Mounting support	DIN rail
Rated operational power in W	24 W
[Us] rated supply voltage	207...253 V AC 50/60 Hz
Output current	1 A
Output voltage	24 V
Connections - terminals	Screw terminals
Height	66.5 Mm 93 mm
Width	87.5 mm
Depth	66.5 mm

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	12.4 cm
Package 1 Length	15.8 cm
Package 1 Weight	795.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	10
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	8.41 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------