



Main

Range of product	SpaceLogic KNX
Product or component type	Dimming actuator
Operating mode	KNX bus system
Bus type	KNX

Complementary

Mounting support	DIN rail
[Ue] rated operational voltage	230 V
Network frequency	50/60 Hz
Number of outputs	2
Load type	LV halogen: 20...350 W at 230 V Incandescent lamp: 20...350 W at 230 V Halogen lamp: 20...350 W at 230 V RC LED lamp: 2...200 W at 230 V RL LED lamp: 2...60 W at 230 V

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.400 cm
Package 1 Width	12.800 cm
Package 1 Length	15.900 cm
Package 1 Weight	269.000 g
Unit Type of Package 2	S04
Number of Units in Package 2	28
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	8.350 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration

RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------