



Main

Range of product	KNX
Product or component type	KNX DALI gateway
Bus type	KNX
Function available	Updateable software

Complementary

Total number of 18 mm modules	4
Mounting support	DIN rail
[Ue] rated operational voltage	100...240 V
Network frequency	50/60 Hz
Communication port protocol	DALI
Local signalling	LED

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.200 cm
Package 1 Width	13.300 cm
Package 1 Length	15.900 cm
Package 1 Weight	228.000 g
Unit Type of Package 2	S04
Number of Units in Package 2	28
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	6.984 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
