



### Main

Range of product	SpaceLogic KNX
Product or component type	Actuator
Operating mode	KNX bus system
Bus type	KNX
Rated output	6 A - 3 x for output switching on/off (heating) 16 A (cooling)

### Complementary

Total number of 18 mm modules	4
Wiring device mounting	DIN rail
[Ue] rated operational voltage	110...240 V
Load type	Valve: 110...240 V AC Fan:

### Environment

IP degree of protection	IP20
-------------------------	------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.800 cm
Package 1 Width	8.500 cm
Package 1 Length	10.300 cm
Package 1 Weight	260.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	6.840 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>