



Main

Range of product	Zelio Count
Product or component type	Hour counter
Display type	Mechanical
Size	48 x 48 mm
Display digits	7 digit(s)
Reset	Without
Technology type	Electromechanical

Complementary

[Us] rated supply voltage	24 V AC 50 Hz Us +/- 10 %
Power consumption in VA	0.08 VA
Backup time	Permanent
Counting mode	Adding 1/100 of an hour
Time range	0...99 999.99 h
Input function	Enable
Input type	Contact
Mounting mode	Flush-mounted
Mounting support	Panel mounting
Fixing mode	By self-locking clamp
Connections - terminals	Screw terminal block
Height	48 mm
Net weight	0.06 kg
Width	48 mm
Character size	5 mm

Environment

Standards	EN 50082-2 EN 50081-2 VDE 0435
Product certifications	UR
IP degree of protection	IP65 conforming to EN/IEC 60529
Ambient air temperature for operation	-10...50 °C
Ambient air temperature for storage	-25...70 °C
Vibration resistance	3 gn (f= 10...150 Hz) conforming to EN/IEC 60068-2-6
Shock resistance	30 gn for 11 ms conforming to EN/IEC 60068-2-27
Electrical shock protection class	Class II conforming to EN/IEC 60536

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	116 g
Package 1 Height	7.8 cm
Package 1 width	11.9 cm
Package 1 Length	15.4 cm

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins


Contractual warranty

Warranty	18 months
----------	-----------


Electromechanical and Electronic Totalizing Timers

Timers with Mechanical Display

XBKH7000000•M




Flush-Mounting



Timers with LCD Display

XBKH81000033E



Flush-Mounting

