



Main

Range of product	Harmony Relay
Product or component type	Plug-in relay
Device short name	RHN
Contacts type and composition	4 C/O
Contact operation	Low level Instantaneous
[Uc] control circuit voltage	220 V AC 50 Hz
[Ithe] conventional enclosed thermal current	1 A 40 °C
Status LED	Without
Control type	Manual control
Coil interference suppression	Without

Complementary

[Ui] rated insulation voltage	250 V
Test levels	Level A group mounting
Operating position	Any position
Minimum switching capacity	50 mVA at 1 mA 50 mVA, 1 V
Contact bounce time	<= 10 ms
Maximum voltage drop	<100 V for 3 A at 24 V
Average resistance	30 mOhm at 20 °C
Average coil consumption in VA	2.5 (holding) at 20 °C 4.5 (inrush) at 20 °C
Control circuit voltage limits	0.8...1.1 Uc conforming to IEC 60255
Drop-out voltage threshold	0.15...0.5 Uc
Cos phi	0.6 (inrush) 0.7 (holding)
Mechanical durability	20000000 cycles
Maximum operating rate	6 cyc/mn
Operating time	2...15 ms between energisation of coil and closing of NO contact at 20 °C 1.2...12 ms between de-energisation of coil and closing of NC contact at 20 °C 1...3 ms for energisation/de-energisation 0.5...6 ms for de-energisation/energisation
CAD overall width	33 mm
CAD overall height	43 mm
CAD overall depth	54 mm
Terminals description ISO n°1	(31-32-34)OC (11-12-14)OC (41-42-44)OC (A1-A2)CO (21-22-24)OC
Net weight	0.09 kg
Compatibility code	RHN

Environment

Standards	NF C 45-250 VDE 0435 IEC 60255 BS 4794
Product certifications	ASE CSA BV USSR EDF UR
Protective treatment	TC
Dielectric strength	2500 V
Ambient air temperature for operation	-5...40 °C conforming to IEC 60255
Ambient air temperature for storage	-40...70 °C
Vibration resistance	6 gn (f= 10...55 Hz) conforming to IEC 60068-2-6 6 gn (f= 10...55 Hz) conforming to NF C 20-616
Shock resistance	50 gn for 11 ms conforming to NF C 20-608

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	100 g
Package 1 Height	5 cm
Package 1 width	5.4 cm
Package 1 Length	7.8 cm
Unit Type of Package 2	S01
Number of Units in Package 2	16
Package 2 Weight	1.738 kg
Package 2 Height	15 cm
Package 2 width	15 cm
Package 2 Length	40 cm

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------