

# TWDXCAISO

serial link tap isolation box - for PLC Twido -  
screw terminal block - 2 RJ45



## Main

Range of product	Twido
Accessory / separate part category	Connection accessories
Accessory / separate part type	Tap isolation box
Accessory / separate part designation	Tap isolation box
Accessory / separate part destination	RS485 serial link
Product specific application	Lines prepolarised (2 R 620 Ohm) RS485 line isolation Line end adaptor (RC 120 Ohm, 1 nF)

## Complementary

Range compatibility	Twido programmable controller Modicon M238 logic controller
[Us] rated supply voltage	24 V
Supply circuit type	DC
Supply	External
Electrical connection	1 screw terminal block 2 connectors RJ45 (for tap-off)
Mounting support	35 mm symmetrical DIN rail
Net weight	0.1 kg

## Packing Units

Package 1 Weight	0.156 kg
Package 1 Height	66.000 mm
Package 1 width	65.000 mm
Package 1 Length	120.000 mm

## Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.