



Main

Range of product	Preventa Safety automation
Product or component type	Preventa safety module
Safety module name	XPSATE
Safety module application	For emergency stop and switch monitoring
Function of module	Emergency stop button with 2 NC contacts
Safety level	<p>Can reach PL d/category 3 time delay safety outputs conforming to EN/ISO 13849-1</p> <p>Can reach PL e/category 4 instantaneous safety outputs conforming to EN/ISO 13849-1</p> <p>Can reach SIL CL 3 instantaneous safety outputs conforming to EN/IEC 62061</p> <p>Can reach SIL CL 2 time delay safety outputs conforming to EN/IEC 62061</p>
Safety reliability data	<p>DC > 99 % conforming to EN/ISO 13849-1 instantaneous safety outputs</p> <p>MTTFd = 134.8 years conforming to EN/ISO 13849-1 instantaneous safety outputs</p> <p>MTTFd = 54.5 years conforming to EN/ISO 13849-1 time delay safety outputs</p> <p>DC > 98.4 conforming to EN/ISO 13849-1 time delay safety outputs</p> <p>PFHd = 6.81E-9 1/h conforming to EN/IEC 62061 instantaneous safety outputs</p> <p>PFHd = 1.96E-8 1/h conforming to EN/IEC 62061 time delay safety outputs</p>
Type of start	Configurable
Connections - terminals	<p>Captive screw clamp terminals, 1 x 0.14...1 x 2.5 mm² flexible with cable end, with double bezel</p> <p>Captive screw clamp terminals, 1 x 0.14...1 x 2.5 mm² solid with cable end, with double bezel</p> <p>Captive screw clamp terminals, 1 x 0.25...1 x 1.5 mm² flexible with cable end, with double bezel</p> <p>Captive screw clamp terminals, 1 x 0.25...1 x 2.5 mm² flexible with cable end, with double bezel</p> <p>Captive screw clamp terminals, 2 x 0.14...2 x 0.75 mm² flexible with cable end, with double bezel</p> <p>Captive screw clamp terminals, 2 x 0.14...2 x 0.75 mm² solid with cable end, with double bezel</p> <p>Captive screw clamp terminals, 2 x 0.25...2 x 1 mm² flexible with cable end, with double bezel</p> <p>Captive screw clamp terminals, 2 x 0.5...2 x 1.5 mm² flexible with cable end, with double bezel</p>
Output type	<p>Relay instantaneous opening, 2 NO circuit(s), volt-free</p> <p>Relay time delay opening, 3 NO circuit(s), volt-free</p>
Number of additional circuits	3 solid state outputs
[Us] rated supply voltage	230 V AC - 20...10 %

Complementary

Synchronisation time between inputs	75 ms
Supply frequency	50/60 Hz
Maximum power consumption in W	8 W
Input protection type	Internal, electronic
Time delay range	0...30 s
[Uc] control circuit voltage	48 V DC

Breaking capacity	180 VA holding AC-15 C300 relay output 1800 VA inrush AC-15 C300 relay output
Breaking capacity	1 A at 24 V (DC-13) time constant: 50 ms for relay output
Output thermal current	2.5 A for time delay outputs 5 A for instantaneous outputs
[Ith] conventional free air thermal current	8 A
Associated fuse rating	4 A gG for time delay outputs conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200 6 A gG for instantaneous outputs conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200
Minimum output current	10 mA for relay output
Minimum output voltage	17 V for relay output
Maximum response time on input open	20 ms
[Ui] rated insulation voltage	300 V (pollution degree 2) conforming to IEC 60947-5-1 300 V (pollution degree 2) conforming to DIN VDE 0110 part 1
[Uimp] rated impulse withstand voltage	4 kV overvoltage category III conforming to IEC 60947-5-1 4 kV overvoltage category III conforming to DIN VDE 0110 part 1
Local signalling	4 LEDs
Mounting support	35 mm symmetrical DIN rail
Net weight	0.38 kg

Environment

Standards	EN/IEC 60204-1 EN/IEC 60947-5-1 EN/ISO 13850
Product certifications	CSA UL TÜV
IP degree of protection	IP20 (terminals) conforming to EN/IEC 60529 IP40 (enclosure) conforming to EN/IEC 60529
Ambient air temperature for operation	-10...55 °C
Ambient air temperature for storage	-25...85 °C

Packing Units

Package 1 Weight	0.497 kg
Package 1 Height	1.250 dm
Package 1 width	0.620 dm
Package 1 Length	1.050 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions

