



### Main

|                                |   |
|--------------------------------|---|
| Range of product               | Canalis   |
| Product name                   | KS  |
| Offer type                     | Standard  |
| Product or component type      | Elbow   |
| Busbar description             | Fire barrier on made to measure                                     |
| Bar material                   | Aluminium   |
| Device application             | Change direction  |
| [Ie] rated operational current | 800 A at 35 °C  |
| Direction change type          | Direction 1: edgewise to right -<br>Direction 1: edgewise to left - |

### Complementary

|                                |                            |
|--------------------------------|----------------------------|
| [Ue] rated operational voltage | 230...690 V                |
| Network frequency              | 50/60 Hz                   |
| Operating angle                | 90 °                       |
| Mounting location              | On trunking                |
| Mounting position              | Any position               |
| Electrical connection          | Lubricated sliding contact |
| Mounting mode                  | By screws                  |
| Width                          | 146 mm                     |
| Depth                          | 111 mm                     |
| Height                         | 290...785 mm               |
| Net weight                     | 24.2 kg                    |

### Environment

|           |                            |
|-----------|----------------------------|
| Standards | IEC 60439-2<br>IEC 61439-6 |
|-----------|----------------------------|

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Weight             | 12.5 kg |
| Package 1 Height             | 16.7 cm |
| Package 1 width              | 84.5 cm |
| Package 1 Length             | 96.7 cm |

### Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Green Premium product   |
| REACH Regulation         |  <a href="#">REACH Declaration</a>             |
| REACH free of SVHC       | Yes   |
| EU RoHS Directive        | Compliant  <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free   | Yes   |
| Mercury free             | Yes   |

|                             |   |
|-----------------------------|---|
| RoHS exemption information  | <a href="#">Yes</a>   |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>   |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free product  |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

