



### Main

Range of product	Canalis
Product name	KS
Offer type	Standard
Product or component type	Elbow
Busbar description	Standard
Bar material	Copper
Device application	Change direction
[Ie] rated operational current	250 A at 35 °C
Direction change type	Direction 1: edgewise to upward -
Colour	White (RAL 9001)

### Complementary

[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
Operating angle	90 °
Busbar trunking polarity	3L + N + PE 3L + PE
Mounting location	On trunking
Mounting position	Any position
Electrical connection	Lubricated sliding contact
Mounting mode	By screws
Width	54 mm
Height	146 mm
Length	250 Mm for side A 250 mm for side B
Net weight	7 kg

### Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Standards	IEC 61439-6 IEC 60439-2

### Packing Units

Package 1 Weight	7.000 kg
Package 1 Height	0.700 dm
Package 1 width	3.200 dm
Package 1 Length	4.000 dm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.