



### Main

Range of product	Canalis
Product name	KS
Product or component type	Feed unit
BAR MATERIAL	Aluminium
Product compatibility	FL21 gland plate
[Ie] rated operational current	800 A 1000 A
Busbar trunking polarity	3L + N + PE
Mounting location	Right
Colour	White (RAL 9001)

### Complementary

Protection type	Circuit breaker protection
[Ue] rated operational voltage	230...690 V
Connections - terminals	Lug
Control type	Rotary handle
Number of circuits	1
Provided equipment	NS800 NS1000
Mounting support	Busbar
Standards	IEC 61439-6 IEC 60439-2
Width	1224 mm
Depth	473.5 mm
Height	500 mm
Body material	Metal
Net weight	51 kg

### Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

### Packing Units

Package 1 Weight	52.000 kg
Package 1 Height	4.790 dm
Package 1 width	5.000 dm
Package 1 Length	12.300 dm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

### Contractual warranty

Warranty	18 months
----------	-----------

