



### Main

Range of product	Canalis
Product name	KS
Product or component type	Feed unit
BAR MATERIAL	Aluminium
Product compatibility	FL21 gland plate
[Ie] rated operational current	800 A 1000 A
Busbar trunking polarity	3L + N + PE
Mounting location	Left
Colour	White (RAL 9001)

### Complementary

Protection type	Circuit breaker protection
[Ue] rated operational voltage	230...690 V
Connections - terminals	Lug
Control type	Rotary handle
Number of circuits	1
Provided equipment	NS800 NS1000
Mounting support	Busbar
Standards	IEC 60439-2 IEC 61439-6
Width	1224 mm
Depth	393.5 mm
Height	500 mm
Body material	Metal
Net weight	51 kg

### Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	59.86 kg
Package 1 Height	47.9 cm
Package 1 width	50 cm
Package 1 Length	123 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months
----------	-----------

