



**Main**

Range of product	Canalis
Product name	KS
Product or component type	Feed unit
BAR MATERIAL	Aluminium
Product compatibility	FL21 gland plate
[Ie] rated operational current	800 A 1000 A
Mounting location	Central
Colour	White (RAL 9001)

**Complementary**

Protection type	Without protection
[Ue] rated operational voltage	230...690 V
Connections - terminals	Lug for 240 mm <sup>2</sup> flexible Lug for 300 mm <sup>2</sup> rigid
Control type	Without
Number of circuits	1
Provided equipment	End cover
Mounting mode	By screws
Mounting support	Busbar
Standards	IEC 61439-6 IEC 60439-2
Width	1101 mm
Depth	411 mm
Height	606 mm
Body material	Metal
Net weight	41.5 kg

**Environment**

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

**Packing Units**

Package 1 Weight	43.000 kg
Package 1 Height	4.180 dm
Package 1 width	6.060 dm
Package 1 Length	11.000 dm

**Offer Sustainability**

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes

---

RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

---

#### Contractual warranty

---

Warranty	18 months
----------	-----------

---

