




Main

Range of product	Canalis
Product name	KS
Product or component type	Feed unit
BAR MATERIAL	Aluminium
Product compatibility	KS NSX250 not included
[Ie] rated operational current	250 A
Busbar trunking polarity	3L + PE
Mounting location	Right
Colour	White (RAL 9001)

Complementary

Protection type	Circuit breaker protection
[Ue] rated operational voltage	230...690 V
Connections - terminals	Lug
Control type	Rotary handle
Number of circuits	1
Mounting support	Busbar
Standards	IEC 60439-2 IEC 61439-6
Width	742 mm
Depth	276 mm
Height	353 mm
Body material	Metal
Net weight	17 kg

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Package 1 Weight	17.300 kg
Package 1 Height	2.180 dm
Package 1 width	3.530 dm
Package 1 Length	7.470 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

