



Main

| | |
|--------------------------------|-----------------|
| Range of product | Canalis |
| Product or component type | Busbar trunking |
| Busbar description | Flexible length |
| Product compatibility | KBB |
| Direction change type | 3 dimensions |
| [Ie] rated operational current | 40 A at 35 °C |

Complementary

| | |
|--|--|
| Device application | Power socket distribution Lighting |
| Thermal stress limit | 900 kA².s |
| Maximum radiated magnetic field | 2 pT |
| [Ue] rated operational voltage | 230...400 V |
| [Uimp] rated impulse withstand voltage | 4 kV |
| [Ui] rated insulation voltage | 690 V |
| [Icw] rated short-time withstand current | 0.94 kA |
| [Ipk] rated peak withstand current | 9.6 kA |
| THDI | 0...15 % 40 A 15...33 % 32 A 33...100 % 28 A |
| Network frequency | 50/60 Hz |
| Control type | Without |
| Number of circuits | 1 |
| Mounting mode | By clips |
| Standards | IEC 61439-6 IEC 60439-2 |
| Width | 540 mm |
| Depth | 51 mm |
| Height | 60 mm |
| Length | 0.5 m |
| Colour | White (RAL 9003) |
| Net weight | 800 g |

Environment

| | |
|---------------------------------------|------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK06 conforming to IEC 62262 |
| Ambient air temperature for operation | 0...35 °C without derating |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 1.4 kg |
| Package 1 Height | 7 cm |
| Package 1 width | 7 cm |
| Package 1 Length | 61 cm |
| Unit Type of Package 2 | P06 |
| Number of Units in Package 2 | 20 |
| Package 2 Weight | 36.5 kg |
| Package 2 Height | 50 cm |
| Package 2 width | 80 cm |
| Package 2 Length | 60 cm |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free | Yes |
| Halogen content performance | Halogen free product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|