



### Main

Range of product	Canalis
Product name	KS
Product or component type	Busbar trunking
Busbar description	Distribution length
BAR MATERIAL	Aluminium
Device application	Medium power distribution
[Ie] rated operational current	500 A at 35 °C
Number of tap-off outlets	10

### Complementary

[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ui] rated insulation voltage	690 V
[Icw] rated short-time withstand current	26.2 kA
[Ipk] rated peak withstand current	55 kA
Electrical connection	Lubricated sliding contact
Radiated magnetic field	0.66 µT
Thermal stress limit	733 kA <sup>2</sup> .s
THDI	0...15 % 500 A 15...33 % 400 A 33...100 % 315 A
Maximum voltage drop	<0.013 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.014 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.014 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.013 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By screws
Mounting position	Horizontal
Neutral position	Up
Busbar trunking polarity	3L + N + PE 3L + PEN
Dimension type	Fix
Width	146 mm
Depth	113 mm
Length	5 m
Net weight	49.55 kg

### Environment

Standards	IEC 60439-2 IEC 61439-6
-----------	----------------------------

### Packing Units

Package 1 Weight	41.875 kg
Package 1 Height	1.700 dm
Package 1 width	1.200 dm
Package 1 Length	51.375 dm

## Contractual warranty

---

Warranty

18 months

---

