



Main

Range of product	Canalis
Product name	KS
Product or component type	Busbar trunking
Busbar description	Fire barrier Transport length
BAR MATERIAL	Copper
Device application	Medium power distribution
[Ie] rated operational current	800 A at 35 °C
Number of tap-off outlets	0

Complementary

[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ui] rated insulation voltage	690 V
[Icw] rated short-time withstand current	37.4 kA
[Ipk] rated peak withstand current	78.7 kA
Electrical connection	Lubricated sliding contact
Radiated magnetic field	1.12 µT
Thermal stress limit	1758 kA².s
THDI	0...15 % 800 A 15...33 % 630 A 33...100 % 500 A
Maximum voltage drop	<0.0083 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.008 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0079 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.0078 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By screws
Mounting position	Horizontal
Neutral position	Up
Busbar trunking polarity	3L + PEN 3L + N + PE
Dimension type	Made to measure
Width	146 mm
Depth	113 mm
Height	900...2340 mm
Net weight	58.5 kg

Environment

Standards	IEC 60439-2 IEC 61439-6
-----------	----------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	60.7 kg
Package 1 Height	16.7 cm
Package 1 width	13 cm
Package 1 Length	247.8 cm